

# **TITAN** **NORTHERN EASYTANK**



## Features & Benefits:

### TANK

#### *Standard Features:*

- 500 – 20,000 Gallon Capacity
- Premium Polyethylene Vertical & Horizontal Storage Tanks
- 2" Layer Closed Cell Foam Insulation
- ISO 22241 Compliant

### CABINET

#### *Mounted Dispense Cabinet Features:*

- 24" W x 48" H x 25" D
- ULCTD10-115V Diaphragm Pump
- Turbine Flow Meter
- 25' Hose Reel
- 650W Heater with Auto Thermostat
- Digital Liquid Level Indicator
- 2" Camlock Fill



### ELECTRICAL REQUIREMENTS

- Requires 115V Circuit
- 30 Amp Dedicated Breaker

### SITE REQUIREMENTS

- Must be installed on level surface
- Crash Protection is recommended
- Additional requirements may be necessary depending upon local or state regulations

## Optional Features:

- Tank Heat Tracing – Maintains a  $\Delta T$  of 40°F
- Pulse Meter

*For use with fuel management systems*

- 2" Standpipe for Tank Monitor Probe
- Submersible Pump

*For use with multiple dispense points*

- 50' Hose Reel



PART #	GALLONS	SHIPPING WEIGHT (LBS)	TANK DIMENSIONS (Dia x Height)	CABINET DIMENSIONS (WxHxD)
905-013-5	500	425	52" x 75"	24" x 48" x 25"
905-017-6	750	488	52" x 105"	24" x 48" x 25"
905-019-5	850	533	52" x 120"	24" x 48" x 25"
905-015-8	1000	514	68" x 82"	24" x 48" x 25"
905-041-3	1050	600	52" x 136"	24" x 48" x 25"
905-012-3	1500	689	68" x 118"	24" x 48" x 25"
905-042-3	2000	860	68" x 154"	24" x 48" x 25"
905-043-3	2100	688	91" x 91"	24" x 48" x 25"
905-044-3	3000	892	99" x 111"	24" x 48" x 25"

\*Tank dimensions include foam insulation and wrap.